



**O’RING METRIČKI ŽENSKI 24° KONUSNI H.T. – DIN 20066/3865
(žicom ubodena matica)**

NP	“	Navoj	Ključ H1	Ključ H2
19	3/4	M 30x2	-	36
25	1	M 36x2	-	41
38	1.1/2	M 52x2	-	60




**O’RING METRIČKI ŽENSKI 24° KONUSNI H.T. – DIN 20066/3865
(pasujuća matica)**

NP	“	Navoj	Ključ H1	Ključ H2
16	5/8	M 30x2	-	36
19	3/4	M 36x2	-	41
25	1	M 42x2	-	50
31	1.1/4	M 42x2	-	50
38	1.1/2	M 52x2	-	60




45° O’RING METRIČKI ŽENSKI 24°KONUSNI H.T. – DIN 20066/3865 (žicom ubodena matica)

NP	“	Navoj	Ključ H1	Ključ H2
19	3/4	M 30x2	-	36
25	1	M 36x2	-	41




45° O’RING METRIČKI ŽENSKI 24° KONUSNI H.T. – DIN 20066/3865 (pasujuća matica)

NP	“	Navoj	Ključ H1	Ključ H2
19	3/4	M 36x2	-	41
25	1	M 42x2	-	50
31	1.1/4	M 52x2	-	60




90° O’RING METRIČKI ŽENSKI 24° KONUSNI H.T. – DIN 20066/3865 (žicom ubodena matica)

NP	“	Navoj	Ključ H1	Ključ H2
19	3/4	M 30x2	-	36
25	1	M 36x2	-	41



**90° O’RING METRIČKI ŽENSKI 24° KONUSNI H.T. – DIN
20066/3865 (pasujuća matica)**

NP	“	Navoj	Ključ H1	Ključ H2
16	5/8	M 30x2	-	36
19	3/4	M 36x2	-	41
25	1	M 42x2	-	50
31	1.1/4	M 52x2	-	60



**METRIČKI MUŠKI 24° KONUSNO SEDIŠTE H.T. – DIN
20066/3861**

NP	“	Navoj	Ključ H1	Ključ H2
19	3/4	M 36x2	36	-
25	1	M 42x2	46	-
31	1.1/4	M 52x2	55	-
38	1.1/2	M 52x2	55	-